
Healthshield 5



HEALTHSHIELD UV Disinfection

UV disinfection systems to deliver safe water without the use of chemicals. Engineered for demanding applications









Healthshield UV Disinfection

The HEALTHSHIELD range of UV systems harness and utilise certain wavelengths of Ultraviolet light which is a natural component of sunlight, falling just below the visible light region of the Electromagnetic spectrum.

The HEALTHSHIELD UV range have the ability to destroy micro-organisms (bacteria, virus, cysts such as Cryptosporidium and Giardia) in water and air by damaging their DNA molecules, thus preventing them replicating and surviving to cause harm.

Ultraviolet disinfection gives safe water without the use of harmful chemicals, does not affect the taste or odour of the water and uses less power than a standard light bulb.

The HEALTHSHIELD range is available for flow rates of 18 L/m up to 1,000 L/m and greater, and includes NSF and USEPA validated systems. Some of the systems incorporate UV sensors to provide continuous readout of UV intensity.

For more information, please call our experts on 1800 656 771 or visit www.southlatration.com.au

Product specifications

Model	Flow Rate*	Pipe Connections	Lamp Power	Lamp Fail Alarm	Volt Free Contacts	UV Intensity
UV-HE 1	8 L/min	15mm	13 watts			
UV-HE 2	18 L/min	15mm	22 watts	•		
UV-HE 3	42 L/min	20mm	30 watts	•		
UV-HE 4	72 L/min	20mm	46 watts	•		
UV-HE 5	130 L/min	25mm	60 watts	•		
UV-HE 6	90 L/min	25mm	48 watts	•	•	
UV-HE 7	155 L/min	25mm	110 watts	•	•	
UV-HE 8	250 L/min	40mm	100 watts	•	•	
UV-HE 9	340 L/min	50mm	2 x 110 watts	•	•	
UV-HE 10	450 L/min	50mm	2 x 100 watts	•	•	
UV-HE 11	130 L/min	25mm	60 watts	•		•
UV-HE 12	150 L/min	25mm	70 watts	•		•
UV-HE 14	230 L/min	40mm	96 watts	•		•
UV-HE 15	454 L/min	50mm	230 watts	•		•
UV-HE 17	1,170 L/min	80mm	320 watts	•		
UV-HE 18	1,170 L/min	80mm	320 watts	•	•**	•
UV-HE 19	1,300 L/min	80mm	400 watts	•		
UV-HE 20	1,300 L/min	80mm	400 watts	•	•**	•
UV-HE 21	2,055 L/min	100mm	550 watts	•		
UV-HE 22	2,055 L/min	100mm	550 watts	•	•**	•

Certified Systems (Flow rates listed are relevant to the specific dose as required by the applicable standard)

PRO10	38 L/min	32mm	120 watts	•	•**	•
PRO20	76 L/min	32mm	160 watts	•	•**	•
PRO30	113 L/min	32mm	230 watts	•	•**	•
PRO50	189 L/min	50mm	230 watts	•	•**	•
PRO24-186	90 L/min	32mm	460 watts	•	•**	•

^{*} Based on 16mJ/cm² dose at 95% UVT. **Optional Extra.

