

S-09-WS


WATER SOFTENER

Single 9" Water Softener

Addresses hard water problems such as calcification, scaling and spotting by removing magnesium and calcium hardness minerals and discarding them to drain.




SOFTENER RESIN



FEATURES

- Save time and reduce labour costs with this preassembled kit
- Easy to order with a single product code
- Free commissioning load of water softener salt
- Reduce equipment maintenance costs with the No Hard Water Bypass Valve option
- Choice of different metered options to suit your requirements
- Suitable for any site application with flexible softener configurations
- Reduced downtime with sequential or parallel controls for multiple softeners

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE

S-09-WS

FLOW RATES

Service Flow (lpm)	19
Peak Service Flow (lpm)	30
Backwash Flow (lpm)	10

OPERATING PRESSURES

Min Operating Pressure	210kPa
Max Operating Pressure	700kPa

CONNECTIONS

Inlet/Outlet Connection size	25mm BSPM
Drain Connection Size	19mm Hose Barb

TEMPERATURE RANGE

5°C - 43°C

WEIGHT

Approximate Operating Weight (kg) 110

ELECTRICAL

Supply 1 x GPO 240V,10Amp

DIMENSIONS

Overall System Width (A)	695mm
Overall System Height (B)	1470mm
Overall System Depth (C)	455mm
Service Clearance (D)	500mm
Service Clearance (E)	500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION

S-10-WS


WATER SOFTENER

Single 10" Water Softener

Addresses hard water problems such as calcification, scaling and spotting by removing magnesium and calcium hardness minerals and discarding them to drain.




SOFTENER RESIN



FEATURES

- Save time and reduce labour costs with this preassembled kit
- Easy to order with a single product code
- Free commissioning load of water softener salt
- Reduce equipment maintenance costs with the No Hard Water Bypass Valve option
- Choice of different metered options to suit your requirements
- Suitable for any site application with flexible softener configurations
- Reduced downtime with sequential or parallel controls for multiple softeners

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE

S-10-WS

FLOW RATES

Service Flow (lpm) 28

Peak Service Flow (lpm) 42

Backwash Flow (lpm) 15

OPERATING PRESSURES

Min Operating Pressure 210kPa

Max Operating Pressure 700kPa

CONNECTIONS

Inlet/Outlet Connection size 25mm BSPM

Drain Connection Size 19mm Hose Barb

TEMPERATURE RANGE

5°C - 43°C

WEIGHT

Approximate Operating Weight (kg) 155

ELECTRICAL

Supply 1 x GPO 240V,10Amp

DIMENSIONS

Overall System Width (A) 730mm

Overall System Height (B) 1625mm

Overall System Depth (C) 455mm

Service Clearance (D) 500mm

Service Clearance (E) 500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION

S-12-WS


WATER SOFTENER

Single 12" Water Softener

Addresses hard water problems such as calcification, scaling and spotting by removing magnesium and calcium hardness minerals and discarding them to drain.




SOFTENER RESIN



FEATURES

- Save time and reduce labour costs with this preassembled kit
- Easy to order with a single product code
- Free commissioning load of water softener salt
- Reduce equipment maintenance costs with the No Hard Water Bypass Valve option
- Choice of different metered options to suit your requirements
- Suitable for any site application with flexible softener configurations
- Reduced downtime with sequential or parallel controls for multiple softeners

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE

S-12-WS

FLOW RATES

Service Flow (lpm)	37
Peak Service Flow (lpm)	56
Backwash Flow (lpm)	20

OPERATING PRESSURES

Min Operating Pressure	210kPa
Max Operating Pressure	700kPa

CONNECTIONS

Inlet/Outlet Connection size	25mm BSPM
Drain Connection Size	19mm Hose Barb

TEMPERATURE RANGE

5°C - 43°C

WEIGHT

Approximate Operating Weight (kg) 210

ELECTRICAL

Supply 1 x GPO 240V,10Amp

DIMENSIONS

Overall System Width (A)	775mm
Overall System Height (B)	1575mm
Overall System Depth (C)	455mm
Service Clearance (D)	500mm
Service Clearance (E)	500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION

S-13-WS


WATER SOFTENER

Single 13" Water Softener

Addresses hard water problems such as calcification, scaling and spotting by removing magnesium and calcium hardness minerals and discarding them to drain.




SOFTENER RESIN



FEATURES

- Save time and reduce labour costs with this preassembled kit
- Easy to order with a single product code
- Free commissioning load of water softener salt
- Reduce equipment maintenance costs with the No Hard Water Bypass Valve option
- Choice of different metered options to suit your requirements
- Suitable for any site application with flexible softener configurations
- Reduced downtime with sequential or parallel controls for multiple softeners

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE

S-13-WS

FLOW RATES

Service Flow (lpm) 50

Peak Service Flow (lpm) 75

Backwash Flow (lpm) 21

OPERATING PRESSURES

Min Operating Pressure 210kPa

Max Operating Pressure 700kPa

CONNECTIONS

Inlet/Outlet Connection size 32mm BSPM

Drain Connection Size 19mm Hose Barb

TEMPERATURE RANGE

5°C - 43°C

WEIGHT

Approximate Operating Weight (kg) 255

ELECTRICAL

Supply 1 x GPO 240V,10Amp

DIMENSIONS

Overall System Width (A) 835mm

Overall System Height (B) 1635mm

Overall System Depth (C) 480mm

Service Clearance (D) 500mm

Service Clearance (E) 500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION

S-14-WS


WATER SOFTENER

Single 14" Water Softener

Addresses hard water problems such as calcification, scaling and spotting by removing magnesium and calcium hardness minerals and discarding them to drain.




SOFTENER RESIN



FEATURES

- Save time and reduce labour costs with this preassembled kit
- Easy to order with a single product code
- Free commissioning load of water softener salt
- Reduce equipment maintenance costs with the No Hard Water Bypass Valve option
- Choice of different metered options to suit your requirements
- Suitable for any site application with flexible softener configurations
- Reduced downtime with sequential or parallel controls for multiple softeners

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE

S-14-WS

FLOW RATES

Service Flow (lpm) 67

Peak Service Flow (lpm) 100

Backwash Flow (lpm) 24

OPERATING PRESSURES

Min Operating Pressure 210kPa

Max Operating Pressure 700kPa

CONNECTIONS

Inlet/Outlet Connection size 32mm BSPM

Drain Connection Size 25mm Hose Barb

TEMPERATURE RANGE

5°C - 43°C

WEIGHT

Approximate Operating Weight (kg) 325

ELECTRICAL

Supply 1 x GPO 240V,10Amp

DIMENSIONS

Overall System Width (A) 865mm

Overall System Height (B) 1910mm

Overall System Depth (C) 480mm

Service Clearance (D) 500mm

Service Clearance (E) 500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION

S-16-WS


WATER SOFTENER

Single 16" Water Softener

Addresses hard water problems such as calcification, scaling and spotting by removing magnesium and calcium hardness minerals and discarding them to drain.




SOFTENER RESIN



FEATURES

- Save time and reduce labour costs with this preassembled kit
- Easy to order with a single product code
- Free commissioning load of water softener salt
- Reduce equipment maintenance costs with the No Hard Water Bypass Valve option
- Choice of different metered options to suit your requirements
- Suitable for any site application with flexible softener configurations
- Reduced downtime with sequential or parallel controls for multiple softeners

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE

S-16-WS

FLOW RATES

Service Flow (lpm) 83

Peak Service Flow (lpm) 125

Backwash Flow (lpm) 34

OPERATING PRESSURES

Min Operating Pressure 210kPa

Max Operating Pressure 700kPa

CONNECTIONS

Inlet/Outlet Connection size 32mm BSPM

Drain Connection Size 25mm Hose Barb

TEMPERATURE RANGE

5°C - 43°C

WEIGHT

Approximate Operating Weight (kg) 485

ELECTRICAL

Supply 1 x GPO 240V,10Amp

DIMENSIONS

Overall System Width (A) 1100mm

Overall System Height (B) 2000mm

Overall System Depth (C) 625mm

Service Clearance (D) 1000mm

Service Clearance (E) 500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION

S-18-WS


WATER SOFTENER

Single 18" Water Softener

Addresses hard water problems such as calcification, scaling and spotting by removing magnesium and calcium hardness minerals and discarding them to drain.




SOFTENER RESIN



FEATURES

- Save time and reduce labour costs with this preassembled kit
- Easy to order with a single product code
- Free commissioning load of water softener salt
- Reduce equipment maintenance costs with the No Hard Water Bypass Valve option
- Choice of different metered options to suit your requirements
- Suitable for any site application with flexible softener configurations
- Reduced downtime with sequential or parallel controls for multiple softeners

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE

S-18-WS

FLOW RATES

Service Flow (lpm)	96
Peak Service Flow (lpm)	150
Backwash Flow (lpm)	41

OPERATING PRESSURES

Min Operating Pressure	210kPa
Max Operating Pressure	700kPa

CONNECTIONS

Inlet/Outlet Connection size	40mm BSPF
Drain Connection Size	40mm BSPF

TEMPERATURE RANGE

5°C - 43°C

WEIGHT

Approximate Operating Weight (kg) 490

ELECTRICAL

Supply 1 x GPO 240V,10Amp

DIMENSIONS

Overall System Width (A)	1160mm
Overall System Height (B)	2100mm
Overall System Depth (C)	625mm
Service Clearance (D)	1000mm
Service Clearance (E)	500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION

S-21-WS


WATER SOFTENER

Single 21" Water Softener

Addresses hard water problems such as calcification, scaling and spotting by removing magnesium and calcium hardness minerals and discarding them to drain.




SOFTENER RESIN



FEATURES

- Save time and reduce labour costs with this preassembled kit
- Easy to order with a single product code
- Free commissioning load of water softener salt
- Reduce equipment maintenance costs with the No Hard Water Bypass Valve option
- Choice of different metered options to suit your requirements
- Suitable for any site application with flexible softener configurations
- Reduced downtime with sequential or parallel controls for multiple softeners

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE

S-21-WS

FLOW RATES

Service Flow (lpm) 117

Peak Service Flow (lpm) 175

Backwash Flow (lpm) 56

OPERATING PRESSURES

Min Operating Pressure 210kPa

Max Operating Pressure 700kPa

CONNECTIONS

Inlet/Outlet Connection size 40mm BSPF

Drain Connection Size 40mm BSPF

TEMPERATURE RANGE

5°C - 43°C

WEIGHT

Approximate Operating Weight (kg) 605

ELECTRICAL

Supply 1 x GPO 240V,10Amp

DIMENSIONS

Overall System Width (A) 1200mm

Overall System Height (B) 2100mm

Overall System Depth (C) 625mm

Service Clearance (D) 1000mm

Service Clearance (E) 500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION

S-24-WS


WATER SOFTENER

Single 24" Water Softener

Addresses hard water problems such as calcification, scaling and spotting by removing magnesium and calcium hardness minerals and discarding them to drain.




SOFTENER RESIN



FEATURES

- Save time and reduce labour costs with this preassembled kit
- Easy to order with a single product code
- Free commissioning load of water softener salt
- Reduce equipment maintenance costs with the No Hard Water Bypass Valve option
- Choice of different metered options to suit your requirements
- Suitable for any site application with flexible softener configurations
- Reduced downtime with sequential or parallel controls for multiple softeners

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE

S-24-WS

FLOW RATES

Service Flow (lpm) 167

Peak Service Flow (lpm) 250

Backwash Flow (lpm) 75

OPERATING PRESSURES

Min Operating Pressure 210kPa

Max Operating Pressure 700kPa

CONNECTIONS

Inlet/Outlet Connection size 40mm BSPF

Drain Connection Size 40mm BSPF

TEMPERATURE RANGE

5°C - 43°C

WEIGHT

Approximate Operating Weight (kg) 850

ELECTRICAL

Supply 1 x GPO 240V,10Amp

DIMENSIONS

Overall System Width (A) 1425mm

Overall System Height (B) 2250mm

Overall System Depth (C) 800mm

Service Clearance (D) 1000mm

Service Clearance (E) 500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION

S-30-WS


WATER SOFTENER

Single 30" Water Softener

Addresses hard water problems such as calcification, scaling and spotting by removing magnesium and calcium hardness minerals and discarding them to drain.




SOFTENER RESIN



FEATURES

- Save time and reduce labour costs with this preassembled kit
- Easy to order with a single product code
- Free commissioning load of water softener salt
- Reduce equipment maintenance costs with the No Hard Water Bypass Valve option
- Choice of different metered options to suit your requirements
- Suitable for any site application with flexible softener configurations
- Reduced downtime with sequential or parallel controls for multiple softeners

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE

S-30-WS

FLOW RATES

Service Flow (lpm) 283

Peak Service Flow (lpm) 425

Backwash Flow (lpm) 113

OPERATING PRESSURES

Min Operating Pressure 210kPa

Max Operating Pressure 700kPa

CONNECTIONS

Inlet/Outlet Connection size 50mm BSPF

Drain Connection Size 50mm BSPF

TEMPERATURE RANGE

5°C - 43°C

WEIGHT

Approximate Operating Weight (kg) 1670

ELECTRICAL

Supply 1 x GPO 240V,10Amp

DIMENSIONS

Overall System Width (A) 1860mm

Overall System Height (B) 2200mm

Overall System Depth (C) 1100mm

Service Clearance (D) 1000mm

Service Clearance (E) 500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION

S-36-WS


WATER SOFTENER

Single 36" Water Softener

Addresses hard water problems such as calcification, scaling and spotting by removing magnesium and calcium hardness minerals and discarding them to drain.




SOFTENER RESIN



FEATURES

- Save time and reduce labour costs with this preassembled kit
- Easy to order with a single product code
- Free commissioning load of water softener salt
- Reduce equipment maintenance costs with the No Hard Water Bypass Valve option
- Choice of different metered options to suit your requirements
- Suitable for any site application with flexible softener configurations
- Reduced downtime with sequential or parallel controls for multiple softeners

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE

S-36-WS

FLOW RATES

Service Flow (lpm) 433

Peak Service Flow (lpm) 650

Backwash Flow (lpm) 163

OPERATING PRESSURES

Min Operating Pressure 210kPa

Max Operating Pressure 700kPa

CONNECTIONS

Inlet/Outlet Connection size 50mm BSPF

Drain Connection Size 50mm BSPF

TEMPERATURE RANGE

5°C - 43°C

WEIGHT

Approximate Operating Weight (kg) 2315

ELECTRICAL

Supply 1 x GPO 240V,10Amp

DIMENSIONS

Overall System Width (A) 2290mm

Overall System Height (B) 2300mm

Overall System Depth (C) 1100mm

Service Clearance (D) 1000mm

Service Clearance (E) 500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION

S-42-WS


WATER SOFTENER

Single 42" Water Softener

Addresses hard water problems such as calcification, scaling and spotting by removing magnesium and calcium hardness minerals and discarding them to drain.




SOFTENER RESIN



FEATURES

- Save time and reduce labour costs with this preassembled kit
- Easy to order with a single product code
- Free commissioning load of water softener salt
- Reduce equipment maintenance costs with the No Hard Water Bypass Valve option
- Choice of different metered options to suit your requirements
- Suitable for any site application with flexible softener configurations
- Reduced downtime with sequential or parallel controls for multiple softeners

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE

S-42-WS

FLOW RATES

Service Flow (lpm) 583

Peak Service Flow (lpm) 875

Backwash Flow (lpm) 224

OPERATING PRESSURES

Min Operating Pressure 210kPa

Max Operating Pressure 700kPa

CONNECTIONS

Inlet/Outlet Connection size 80mm BSPF

Drain Connection Size 80mm BSPF

TEMPERATURE RANGE

5°C - 43°C

WEIGHT

Approximate Operating Weight (kg) 2780

ELECTRICAL

Supply 1 x GPO 240V,10Amp

DIMENSIONS

Overall System Width (A) 3000mm

Overall System Height (B) 2900mm

Overall System Depth (C) 1400mm

Service Clearance (D) 1000mm

Service Clearance (E) 500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION

S-48-WS


WATER SOFTENER

Single 48" Water Softener

Addresses hard water problems such as calcification, scaling and spotting by removing magnesium and calcium hardness minerals and discarding them to drain.



SOFTENER RESIN



FEATURES

- Save time and reduce labour costs with this preassembled kit
- Easy to order with a single product code
- Free commissioning load of water softener salt
- Reduce equipment maintenance costs with the No Hard Water Bypass Valve option
- Choice of different metered options to suit your requirements
- Suitable for any site application with flexible softener configurations
- Reduced downtime with sequential or parallel controls for multiple softeners

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE

S-48-WS

FLOW RATES

Service Flow (lpm)	733
Peak Service Flow (lpm)	1100
Backwash Flow (lpm)	292

OPERATING PRESSURES

Min Operating Pressure	210kPa
Max Operating Pressure	700kPa

CONNECTIONS

Inlet/Outlet Connection size	80mm BSPF
Drain Connection Size	80mm BSPF

TEMPERATURE RANGE

5°C - 43°C

WEIGHT

Approximate Operating Weight (kg) 3295

ELECTRICAL

Supply 1 x GPO 240V,10Amp

DIMENSIONS

Overall System Width (A)	3200mm
Overall System Height (B)	2900mm
Overall System Depth (C)	1400mm
Service Clearance (D)	1000mm
Service Clearance (E)	500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION

S-63-WS


WATER SOFTENER

Single 63" Water Softener

Addresses hard water problems such as calcification, scaling and spotting by removing magnesium and calcium hardness minerals and discarding them to drain.



SOFTENER RESIN



FEATURES

- Save time and reduce labour costs with this preassembled kit
- Easy to order with a single product code
- Free commissioning load of water softener salt
- Reduce equipment maintenance costs with the No Hard Water Bypass Valve option
- Choice of different metered options to suit your requirements
- Suitable for any site application with flexible softener configurations
- Reduced downtime with sequential or parallel controls for multiple softeners

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE

S-63-WS

FLOW RATES

Service Flow (lpm) 1167

Peak Service Flow (lpm) 1300

Backwash Flow (lpm) 504

OPERATING PRESSURES

Min Operating Pressure 210kPa

Max Operating Pressure 700kPa

CONNECTIONS

Inlet/Outlet Connection size 80mm BSPF

Drain Connection Size 80mm BSPF

TEMPERATURE RANGE

5°C - 43°C

WEIGHT

Approximate Operating Weight (kg) 5200

ELECTRICAL

Supply 1 x GPO 240V,10Amp

DIMENSIONS

Overall System Width (A) 3600mm

Overall System Height (B) 3000mm

Overall System Depth (C) 1700mm

Service Clearance (D) 1000mm

Service Clearance (E) 500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION