PuROtherm®

MICRO PRE-TREATMENT

Ensure optimum RO system performance with an integrated pre-treatment system that includes sediment filtration, softening, and carbon filtration, all designed for easy installation and maintenance.



PRE-TREATMENT UNIT FOR THE PUROTHERM MICRO

FEATURES

- Improve water clarity and quality by removing suspended solids, turbidity, and particulates through effective sediment filtration.
- Prevent scaling and extend RO membrane life with water softening that removes hardness ions.
- Enhance RO system performance by removing chlorine, organic compounds, and other contaminants through activated carbon filtration.
- Easily monitor and validate water quality with two hygienic sample valves, ensuring consistent performance.
- Simplify installation and save space with a modular, compact design, fitting into areas as small as 580mm wide x 760mm deep x 1960mm high (Approx.).

Freecall 1800 656 771 southlandfiltration.com.au





OPERATIONAL REQUIREMENTS

| FEED WATER QU | JALITY | |
|--------------------------------|---|--|
| Conductivity (µS/cr | m) – | |
| Total Dissolved Solids (TDS) - | | |
| Hardness as CaCO3 (mg/l) - | | |
| Temperature (°C) - | | |
| Fouling Index (SDI) - | | |
| Free Chlorine (mg/l) - | | |
| Reactive Silica (mg/l) - | | |
| Pressure (kPa) | 400-600kPa | |
| PRODUCT WATER QUALITY | | |
| AS 5369:2023 (Table 7.2) | Softened water suitable for the Purotherm Micro | |
| WEIGHT (KG) | | |
| Wet | - | |
| Dry | - | |
| DIMENSIONS (MM) | | |
| Width | 580mm | |
| Depth | 760mm | |
| Height | 1960mm | |


| UNIT SPECIFICATIONS | |
|-----------------------------|----------------------|
| Distribution pump (I/min) | - |
| Permeate Rate at 15°C (I/h) | - |
| Storage tank volume (L) | - |
| Delivery Temperature (°C) | Ambient |
| Max Ringmain Length (m) | - |
| Maintenance Access | 500mm x 1800mm |
| Noise Level (dB) | - |
| Power Supply | 10amp GPO |
| Ringmain Connection | - |
| Inlet Connection | 1" inlet / 1" outlet |
| Drainage Requirement | 2"PVC connection |


| CONSUMABLES & ACCESSORIES | | |
|---------------------------|---|-----------------------------------|
| Part Number | Description | Typical Annual Requirement (M/A)w |
| S15151002 | SKAN Polyspun Sediment Filter Cartridge, Large Diameter 20"x4.5", 5 micron | Dependant on Feed water quality |
| S15403002 | SKAN Carbon Block Filter Cartridge 20"x4.5", Large Diameter, 10 micron | Dependant on Feed water quality |
| SALT15-BAG | Softener Salt, 15kg Bag | Dependant on Feed water quality |

Freecall 1800 656 771 southlandfiltration.com.au



PLANS/DRAWINGS





Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771 southlandfiltration.com.au

