

SLB-PP-PT

SKAN BAG FILTERS

Versatile solution for water, oils, chemicals, beverages, paints, offering simplicity, speed, and cost-effectiveness over complex systems.



SLB-PP SERIES

FEATURES

- Flows up to 3.0 L/s
- Durable reinforced polypropylene housings
- Pressure relief / bleed valve
- Supplied with wall-mount bracket and spanner
- Max operating pressure: 620kPa
- 40mm (1½") BSPF Inlet/Outlet

PLANS/DRAWINGS



OPERATIONAL REQUIREMENTS

PRODUCT CODE

S05101001

FLOW RATES (M³/HR)

Max Flow Rate 10.8m³/hr

TEMPERATURE

Max temperature 38°C

OPERATING PRESSURES (KPA)

Max operating pressure 620 kpa

CONNECTIONS

Inlet/Outlet (BPSM) 1½" BSPF (40mm)

FILTER SURFACE AREA (M²)

0.112

MICRON RATINGS AVAILABLE

1um, 5um, 10um, 20um, 50um, 100um

WEIGHT (KG)

Packaged (kg) 4kg

Empty 3.5kg

In service (water) 10.0kg

INSTALLED DIMENSIONS (MM)

Height 606

Width 184

Depth 185

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
FILTRATION