

AM 200 3"**AUTOMATIC
BACKWASH FILTER**

A compact, durable filtration system delivering exceptional 3–6 micron protection with rapid self-cleaning performance and minimal maintenance.




**SEAWATER FILTER****FEATURES**

- **Exceptional filtration:** 3–6 micron screen protects pumps and equipment without daily maintenance.
- **Space-smart modular design:** Installs easily in tight or complex spaces, ideal for ships and plant rooms.
- **Fast, automatic backwash:** Cleans in just 6 seconds without stopping system flow, using minimal water.
- **Quick screen swaps:** Replace filter screens in minutes — reduces downtime and labour costs.
- **Maintenance-free & eco-friendly:** No disposable bags or cartridges — lower waste, lower cost.
- **Built to last:** FRP-reinforced body provides corrosion resistance and long service life.
- **Premium stainless steel screen:** Super duplex steel ensures strength, durability, and reliability.

Freecall 1800 656 771
southlandfiltration.com.au

 **southland**
FILTRATION

PLANS/DRAWINGS



OPERATIONAL REQUIREMENTS

PRODUCT CODE	
S25200501	
FLOW	
Service Flow (Lpm)	1000
Backwash Flow (Lpm)	200
PRESSURE	
Min Operating Pressure	200kPa
Max Operating Pressure	1000kPa
CONNECTIONS	
Inlet/Outlet Connection size	87.88mm BSPM (3")
Drain Connection Size	50mm (2") Hose Barb

TEMPERATURE (°C)	
Temperature Range	0°C – 70°C
WEIGHT (KG)	
Approximate Operating Weight	90kg filled
POWER	
Power Supply	1 x GPO 230V, XXAmp
DIMENSIONS (MM)	
Width	1294
Depth	500
Height	400
Service Clearance D	500

1225V1.0

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION