

Pure Loop

PURE WATER STORAGE AND DISTRIBUTION SYSTEM



For the safe storage and distribution of purified water including Types 1, 2 & 3


FEATURES

- Monitor & Protect Remotely - Peace of mind with continuous oversight. Pressure, temperature, and water quality are tracked 24/7, with remote login and BMS integration. Automated tank draining prevents issues before they escalate. Password protection secures your system against unauthorised changes.
- Pure Water Assurance - Stable, compliant water quality every time. CO² removal vents prevent chemistry disruption and resistivity loss. Choose a standard vent or CO² scrubber for high-purity applications.
- Consistent Pure Water - Always ready when you need it. Recirculation through UV and endotoxin filters keeps RO water pure and bacteria-free. Stores 500 L or 1,000 L while maintaining chemical and mineral integrity.
- PVDF Piping for Ultra-Pure Applications - No leaching, no contamination. UV-stabilised PVDF piping preserves water chemistry across all grades (Type 1, 2, 3) and protects process integrity.

Freecall 1800 656 771
southlandfiltration.com.au

 **southland**
FILTRATION

PLANS/DRAWINGS



SPECIFICATIONS

PRODUCT CODE
PLx/x/x-x-x-x-x
SERVICE FLOW (LPM)
30 - 120 litres/minute
OPERATING PRESSURE
Min e.g. 240kPa
Max e.g. 700kPa
LOOP CONNECTION
1" Sanitary fitting (Triclover)
DRAIN CONNECTION SIZE (MM) HOSE BARB
25mm
TEMPERATURE RANGE
5°C - 43°C

APPROXIMATE OPERATING WEIGHT (KG)	
700kg	
SUPPLY	
240 VAC, 415 VAC	
DIMENSIONS	
Width (mm)	840mm
Depth (mm)	1095mm
Height (mm)	1720mm
Service Clearance D	500mm
Service Clearance E	500mm

Disclaimer. Southland Filtration reserves the right to, at any time change any details of design, specifications and performance figures of any published data.

Freecall 1800 656 771
southlandfiltration.com.au

southland
 FILTRATION